



- Double mechanical seal for great reliability, reduction of maintenance operations and continuous duty.
- Very high flow and pressure
- Stainless steel pump body
- Stainless steel motor shaft
- Integrated check valve
- For very deep wells


Model: **SUB 6000/75 Plus**
 Part number: **N32000240**
 Barcode: **7630014535323**

Submersible pump with asynchronous single phase motor, stainless steel pump body and motor shaft. SUB 6000/75 Plus is ideal for pumping water from very deep wells or from wells that are located far away from water sources, thanks to the high pressure performances.



APPLICATIONS

- Irrigation of lawns and flowerbeds
- Washing of terraces or outdoors floors
- Basins or expansion tanks filling/draining

ABSORBED POWER	1300 W	POWER CABLE	30 m H07 RN8-F
VOLTAGE	230 V	SUCTION/DELIVERY PORT.	41.90 mm (1 1/4)
FLOW RATE	6000 l/h	MAX.WATER TEMPERATURE	40°C
PRESSURE/MAX.HEAD	71 m / 7.1 bar	WEIGHT	12.5 Kg
RATED CURRENT	6 A	PACKAGING DIMENSIONS	80 x 22.5 x 10.5 cm
N° IMPELLERS	10	PCS PER PALLET	30
MIN.OPERATING SPACE	100 mm	ACCESSORIES	-
MAX.IMMERSION DEPTH	27 m		x 7